



**TECNO-CENTER C.A.**

*Equipos de laboratorio y procesos*

RIF: J-07550070-9



## **SHS Sensor Built-in Motorized Calibration Weight Water and Dust proof IP65**



### **Features** [Details](#)

- ▶ Fast, new Super Hybrid Sensor (SHS) gives you the ultimate in response speed - Just 1.5 Second!
- ▶ Internal Calibration and Internal Calibration Mass makes calibrating your GX-K easier.
- ▶ Automatic Self-Calibration calibrates the balance when it detects changes in the ambient temperature
- ▶ Water and Dust Proof IP65
- ▶ Standard RS-232C
- ▶ Standard Windows Communication Tools Software
- ▶ Large, bright Vacuum Fluorescent Display - see the display even in the dark
- ▶ Percentage, Counting Functions & Comparator functions
- ▶ ACAI Counting Function for highly accurate counting
- ▶ GLP/GMP/ISO Compliance
- ▶ ID Number The balance ID number can be set. It is used to identify the balance when GLP is used.

The ID number is memorized and maintained once it is fixed, even if the AC adapter is removed.

- ▶ Display Auto Power Off Function Display turns off after 10 minutes of inactivity (can be disabled when undesired)
- ▶ Auto Power On Function Plug it in and it turns itself on without pressing ON/OFF key

▶Data Memory Function

Format the Data Memory Function for:

-200 sets of weighing data, -100 sets of weighing data with Time & Date, -50 sets of GLP Data - Time & Date,

Calibration Data, ID number and Serial number or -50 sets of Unit Weight for Counting Mode, -20 sets Comparator

setting Value or -20stes Tare Weight Value.

▶Smart Range Function(GX-8K,GX-32K) □Fine weighing is possible even with a heavy container for more accuracy.

▶Auto Re-Zero Function Re-Zeroes automatically after data output

▶Auto Self Checking Automatically checks itself when setting the Automatic Adjustable Environment

## Options

GX-04K Comparator Output with Buzzer/ RS232C / Current loop output \*1

GX-06K Analog Output / Current loop output \*1

GX-07K Waterproof RS232C cable \*2

\*1 □04K, 06K and the RS232C (provide as standard) cannot be used at the same time. Water and dust proof specifications cannot be applied when the GX-04K and GX-06K is installed.

\*2 Use the GX-07K, optional water proof RS232C cable, in order to use the standard RS232C interface for water and dust proof(IP65).

Model	Capacity	Resolution	Pan Size
GX-8K	8.1kg	0.01g	270(W) x210(D)mm
GX-8K2	8.1kg / 2.1kg	0.1g / 0.01g	270(W) x210(D)mm
<b>GX-10K</b>	<b>10.1kg</b>	<b>0.01g</b>	<b>270(W) x210(D)mm</b>
GX-12K	12kg	0.1g	270(W) x210(D)mm
GX-20K	21kg	0.1g	270(W) x210(D)mm
GX-30K	31kg	0.1g	270(W) x210(D)mm
GX-32K	31kg / 6.1kg	1g / 0.1g	270(W) x210(D)mm